





Nomad Power offers a line-up of high performance and zero maintenance commercial deep cycle batteries. The NOMAD POWER E2 has an extreme long design life (10 years) with zero maintenance required. Created for long life high cycle application such as solar and wind powered renewable energy The NOMAD POWER E2 storage. range are well known for stable and reliable performance. The battery can withstand overcharge, over discharge, vibration and shocks. It is also capable of extended storage, UPS, Standby or Cyclic Applications.

## APPLICATIONS

2	Telecommunications
2	Solar system
2	Wind power system
2	Engine starting
2	Wheelchair
2	Floor cleaning machines
2	Golf trolley
9	Boats

## CYCLE LIFE VS. DEPTH OF DISCHARGE



## SPECIFICATION

Nominal Voltage	12V		
Nominal Capacity(100HR)	22.0AH		
Dimension	Length Width Container Height Total Height (with Terminal)	181 ± 1mm (7.14 inches) 76 ± 1mm (3.03 inches) 167 ± 1mm (6.59 inches) 167 ± 1mm (6.59 inches)	
Approx Weight	Approx 6.0 kg		
Terminal	ТЗ		
Container Material	ABS		
Rated Capacity	22.0 AH/0.22A (10 19.4 AH/0.95A (2 18.5 AH/1.85A ( 16.0 AH/3.20A 14.5 AH/4.83A 11.7 AH/11.7A	0hr, 1.80V/cell, 30°C/86°F) 0hr ,1.80V/cell,30°C/86°F) 10hr,1.80V/cell,30°C/86°F) (5hr,1.75V/cell,30°C/86°F) (3hr,1.75V/cell,30°C/86°F) (1hr,1.60V/cell,30°C/86°F)	
Max. Discharge Current	255A (2s)		
Internal Resistance	Approx 16mΩ		
Operating Temp.Range	Discharge : -15 ~ 50°C (5 ~ 122°F) Charge : 0 ~ 40°C (32 ~ 104°F) Storage : -15 ~ 40°C (5 ~ 104°F)		
Nominal Operating Temp. Range	27 ± 3°C (80 ± 5°F)		
Cycle Use	Initial Charging Current less than 6.0A.Voltage 14.4V~14.7V at 25°C(77°F)Temp. Coefficient -30mV/°C		
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C		
Capacity affected by Temperature	40°C (104 °F) 103% 30°C (86 °F) 100% 0°C (32 °F) 86%		
Self Discharge	NOMAD POWER E2 series batterys may be stored for up to 3 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.		

## TERMINAL PHOTO



www.nomadpower.net

© 2015 Nomad Power Systems. All Rights Reserved.

All trademarks owned by Nomad Power Systems or its affiliated companies.