





Nomad Power offers a line-up of high performance and zero maintenance commercial deep cycle batteries. The NOMAD POWER E2 has an extreme long design life (10 years) with zero maintenance required. Created for long life high cycle application such as solar and wind powered renewable energy storage. The NOMAD POWER E2 is suitable for solar and wind powered homes, TV / Radio stations and solar powered equipment. Additionally the High Cold Cranking Amps available make it suitable for a long-life dual use battery for marine and motorhome use.

APPLICATIONS

- Telecommunications
- Solar system
- Wind power system
- Engine starting
- Wheelchair
- Floor cleaning machines
- Golf trolley
- Boats

SPECIFICATION

Nominal Voltage	12V
Nominal Capacity(100HR)	270.0AH
Dimension	Length 522 ± 3 mm (20.55 inches)Width 240 ± 2 mm (9.45 inches)Container Height 218 ± 2 mm (8.58 inches)Total Height (with Terminal) 224 ± 2 mm (8.81 inches)
Approx Weight	Approx 59.5 kg (131.1 lbs)
Terminal	T11
Container Material	ABS
Rated Capacity	270.0 AH/2.7A (100hr, 1.80V/cell, 30°C/86°F) 220.4 AH/11.0A (20hr ,1.80V/cell, 30°C/86°F) 210.0 AH/21.0A (10hr,1.80V/cell,30°C/86°F) 181.3 AH/36.3A (5hr,1.75V/cell,30°C/86°F) 164.0 AH/54.7A (3hr,1.75V/cell,30°C/86°F) 134.1 AH/134.1A (1hr,1.60V/cell,30°C/86°F)
Max. Discharge Current	1000A (2s)
Internal Resistance	Approx 2.7mΩ
Operating Temp.Range	Discharge: -15 ~ 50°C (5 ~ 122°F) Charge: 0 ~ 40°C (32 ~ 104°F) Storage: -15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	27 ± 3°C (80± 5°F)
Cycle Use	Initial Charging Current less than 50.0A.Voltage 14.4V~14.6 at 25°C(77°F)Temp. Coefficient -30mV/°C
Standby Use	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C
Capacity affected by Temperature	40°C (104 °F) 102% 30°C (86 °F) 100% 0°C (32 °F) 86%
Self Discharge	NOMAD POWER E2 series batterys may be stored for up to 3 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.

CYCLE LIFE VS. DEPTH OF DISCHARGE

Testing condition

Discharging:current 0.17C (FV 1.7V/cell); Charging:current 2.45V/cell, max. 0.25CA; Charging volume:125% of discharged capacity.

Number of Cycles

TERMINAL PHOTO

