MARINE 600







True Sinewave output



High Operating efficiency



Field Serviceable



Automatic temperature and voltage protection



Rugged die-cast aluminium chassis



Designed for recreational and industrial marine applications. Nomad Marine inverters are suitable for both heavy duty and sensitive electronic loads. With less than 3% harmonic distortion, the Nomad Marine delivers a true sine wave output that is identical to grid supply AC power. Designed for power tools, household equipment, marine electronics and more.

M606

Flootvicel		M000 40	M000 04	M000 40
Electrical		M606-12	M606-24	M606-48
Nominal DC input Voltage		12V DC	24V DC	48V DC
Continous Power Rating		600 watts	600 watts	600 watts
AC Voltage/Frequency		110V/60Hz	110V/60Hz	110V/60Hz
Continuous AC RMS Output		2.6 Amps	2.6 Amps	2.6 Amps
Idle Power		4 watts	8 watts	13 watts
Typical Efficiency		87%	88%	90%
AC Overload Capability	Surge (5ms)	1200 VA	1200 VA	1200 VA
	10 Seconds	720 VA	720 VA	720 VA
	24 Hours	480 VA	480 VA	480 VA
DC Input Voltage Range		10.6V to 15.5V	21.6V to 30V	43.2V to 63V
Low Voltage Alarm		10.5V	21V	41.8V
Low Voltage Shutdown		9.5V	19V	38V
Over voltage protection		16V	31V	65V
Low Voltage Recovery		11.8V	23.6V	47.2V
Over voltage recovery		15.7V	31.8V	63V
Protecion Functions				
Low voltage LED red light, buzzer warning, automatic recovery			Short circuit within 2 seconds automatic recovery	
Over voltage LED red light, automatic recovery			Input reverse connection, Fuse burn-out	
Over-load LED red light, automatic recovery			Over temperature LED red light, buzzer warning, automatic recover	

General

Temperature Range	-10C to +50 C
Weight	1.5kg
Dimensions (H x W x L)	24 x 11.8 x 6.3 cm